

# PRIMEMASTER PRIMER / SEALER

## MATERIAL SAFETY DATA SHEET



### PRODUCT IDENTIFICATION

**Master Coating Technologies**

2740 31st Avenue South

Minneapolis, MN 55406

612.722.8808

Trade Name: **Scuffmaster Primemaster Primer/Sealer**

Chemical Family: Latex Emulsion/Pigment Dispersion

**Medical & Transport Emergency Contact:****INFOTRAC: 1.800.535.5053**

MSDS Date: 07.24.2001

DOT Classification: Not Regulated

CAS Number: Mixture

Supersedes: All Previous

### PHYSICAL DATA

Boiling Range (F): 212° (water)

Freezing Point (F): 32° (water)

Vapor Density (Air=1): &lt;1

Vapor Pressure (mmHg @ 68° F): 17

Evaporation Rate (Butyl Acetate = 1): 1 (water)

Solubility in Water: Dilutable

Specific Gravity: 1.2

% Volatile by Weight: 59

pH Information: 9.0 - 10.0

Appearance &amp; Odor: Liquid, white colors, latex smell

### HAZARDOUS INGREDIENTS

Ingredient	Percent	PPM	MG/M3	CAS Number
None	N/A	N/A	N/A	N/A

**This paint mixture contains** titanium dioxide and/or other pigments classified by ACGIH as "nuisance dusts." Exposures to spray mist or sanding dust should be controlled to below 10mg/m3 through usage of NIOSH/MSHA TC23C or equivalent approved dust filter respirators. Follow respirator manufacturer's directions for use.

**SECTION 313 SUPPLIER NOTIFICATION:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CRF 372. NONE above the minimum concentrations.

**HMIS Rating:** Health = 1 Flammability = 0 Reactivity = 0 Personal Protection = B\*  
\*User should determine appropriate personal protective equipment based on use conditions.

### HEALTH HAZARD DATA

**Entry Routes:** Inhalation, Ingestion, Skin Contact, Eye Contact **Effects of Overexposure:** N/A **Effects of Inhalation:** Trace component, residual monomer, and other organics may be irritating to the eyes, skin, mucous membranes, respiratory tract and may produce symptoms of headache and nausea in poorly ventilated areas. **Effects of Ingestion:** Irritating to gastrointestinal tract, abdominal pain, and diarrhea. **Effects of Skin Contact:** Prolonged contact can cause transient reddening of the skin. **Effect of Eye Contact:** Direct contact may be irritating to eyes. **Effects of Repeated Overexposure:** This paint mixture as provided shows no evidence of chronic effects from available information.

## PRIMER/SEALER – MATERIAL SAFETY DATA SHEET ( continued )

### EMERGENCY FIRST AID PROCEDURES

**Eye Contact:** Immediately flush eyes for 15 minutes occasionally lifting eyelids. If victim wears contact lenses, remove lenses and continue rinsing. Clean lenses before reusing. If irritation continued, consult a physician. **Skin Contact:** Wash effected area thoroughly with mild soap and water. If irritation develops and persists, consult a physician. **Inhalation:** Move to fresh air if necessary. If irritation persists, consult a physician. If victim is not breathing, artificial respiration should be administered by qualified personnel. Seek immediate medical attention. **Ingestion:** If swallowed, give lots of water, and induce vomiting. If necessary consult a physician.

### FIRE & EXPLOSION HAZARD DATA

Flash Point: Not determined (aqueous system)

LEL: Not determined (aqueous system)

UEL: Not determined (aqueous system)

**Special Fire Fighting Procedures:** Use breathing apparatus when fighting enclosed fires.

#### Fire Extinguishing Media:

Non-Flammable (aqueous emulsion)

If water evaporates, remaining material can burn.

Use all-purpose foam for large fires, and CO<sub>2</sub> or dry chemical media for small fires.

#### Unusual Fire and Explosion Hazard:

Products will not burn but may spatter if temperature exceeds boiling point of water. Dried solids can burn, giving off oxides and carbon.

### REACTIVITY DATA

**This product** is stable under normal (ambient) conditions and hazardous polymerization will not occur. **Hazardous Decomposition Products:** Combustion of dried film may produce carbon dioxide and carbon monoxide. **Conditions or Materials to Avoid:** None.

### SPILL OR LEAK PROCEDURES

**Spill:** Major spills should be collected for disposal. Minor spills may be flushed to sewer if permitted by local, state, and federal regulations.

**Waste Disposal:** Incinerate or bury in suitable landfills where permitted by appropriate government regulations.

### SPECIAL PROTECTION INFORMATION

**Respiratory Protection:** Use appropriate MAHA/NIOSH approved respirator in areas with poor ventilation and when exposed to spray mists or sanding dusts. **Ventilation:** General room ventilation is expected to be satisfactory. Use local exhaust if needed for mist or vapor.

**Protective Gloves:** Wear gloves impervious to water and soap. **Eye Protection:** Wear goggles if spraying and available eye bath.

---

**Disclaimer:** The information in this MSDS was obtained from sources we believe are reliable. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness. **The conditions or handling, storage, use and disposal of the product** are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product. **Disposal of containers** should be in accordance with applicable federal, state and local laws and regulations.

---

Thank you for selection Scuffmaster.

---

technical support: 1.800.898.0219

documents: [www.scuffmaster.com](http://www.scuffmaster.com)

---

