

SOLID METAL

MATERIAL SAFETY DATA SHEET



Pretty. Tough. Paint.

INCLUDES

Solid Metal consists of Metalli-Coat 2000TM and Ultra-ClearTM. Below are the MSDS sheets for both.

METALLI-COAT 2000

MATERIAL SAFETY DATA SHEET



Pretty. Tough. Paint.

PRODUCT IDENTIFICATION

Master Coating Technologies

2777 Eagandale Blvd.

Eagan, MN 55121

612.722.8808

Trade Name: **Scuffmaster Metalli-Coat 2000**

Chemical Family: Urethane/Acrylic Metallic Pigment Dispersion

Medical & Transport Emergency Contact:

INFOTRAC: **1.800.535.5053**

MSDS Date: 07.02.2004

DOT Classification: Not Regulated

Supersedes: All Previous CAS Number: Mixture

Synonyms: MC2000, 7226

PHYSICAL DATA

Boiling Range (F): 212 (water)

Freezing Point (F): 32 (water)

Vapor Density (Air=1): <1

Vapor Pressure (mmHg @ 68° F): 17

Evaporation Rate (Butyl Acetate = 1): 1 (water)

Solubility in Water: Dilutable

Specific Gravity: 1.1 - 1.3

% Volatile by Weight: 47.5

pH Information: 9.0 - 10.0

VOC: 139 g/L

Appearance & Odor: Liquid, metallic colors, latex odor

HAZARDOUS INGREDIENTS

Ingredient	Percent	PPM	MG/M3	CAS Number
Propylene Glycol	1 - 2	300	N/A	57-55-6
Esther Alcohol	1 - 2	None Established	N/A	25265-77-4
Aluminum Flake	5 - 15	N/A	15-OSHA PEL & 10-ACGIH TLV	7429-90-5
Stoddard Solvent	1 - 2	N/A	525-OSHA PEL & 525-ACGIH TLV	8052-41-3
Aromatic Solvent	1 - 2	N/A	245 - Supplier Recommendation	64742-95-6

This paint mixture contains titanium dioxide and/or other pigments classified by ACGIH as "nuisance dusts." Exposures to spray mist or sanding dust should be controlled to below 10mg/m3 through usage of NIOSH/MSHA TC23C or equivalent approved dust filter respirators. Follow respirator manufacturer's directions for use.

SECTION 313 SUPPLIER NOTIFICATION: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CRF 372. NONE above the minimum concentrations.

HMIS Rating: Health = 1 Flammability = 1 Reactivity = 0 Personal Protection = B*

*User should determine appropriate personal protective equipment based on use conditions.

HEALTH HAZARD DATA

TOXICITY DATA: SOLVENTS: Oral LD₅₀ rat > 5000 mg/kg (essentially nontoxic) – dermal LD₅₀ rabbit > 3160 mg/kg (slight toxic)

ALUMINUM: None. No toxic effects are known.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE AND ROUTES OF ENTRY. Entry Routes: Inhalation, Ingestion, Skin Contact, Eye Contact

Effects of Overexposure: N/A **Effects of Inhalation:** Trace component, residual monomer, and other organics may be irritating to the eyes, skin, mucous membranes, respiratory tract and may produce symptoms of headache and nausea in poorly ventilated areas. **Effects of Ingestion:**

DO NOT INGEST. While aluminum content is non-toxic and the solvents are only slightly toxic by oral ingestion, minute amounts of certain portions

MC2000 – MATERIAL SAFETY DATA SHEET (continued)

HEALTH HAZARD DATA (continued)

of the solvents, if aspirated into the lungs during ingestion, may cause severe pulmonary injury or death. **Effects of Skin Contact:** Prolonged contact can cause transient reddening of the skin. **Effect of Eye Contact:** Direct contact may be irritating to eyes. **Effects of Repeated Overexposure:** This paint mixture as provided shows no evidence of chronic effects from available information.

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Immediately flush eyes for 15 minutes occasionally lifting eyelids. If victim wears contact lenses, remove lenses and continue rinsing. Clean lenses before reusing. If irritation continued, consult a physician. **Skin Contact:** Wash effected area thoroughly with mild soap and water. If irritation develops and persists, consult a physician. **Inhalation:** Move to fresh air if necessary. If irritation persists, consult a physician. If victim is not breathing, artificial respiration should be administered by qualified personnel. Seek immediate medical attention. **Ingestion:** If swallowed, give lots of water, and induce vomiting. If necessary consult a physician.

FIRE & EXPLOSION HAZARD DATA

Flash Point: 104° F (40°C) Minimum (Method - Setaflash)

LEL: Not determined (aqueous system)

UEL: Not determined (aqueous system)

Fire Extinguishing Media:

Use Class B and Class D extinguishers

Special Fire Fighting Procedures:

Use breathing apparatus when fighting enclosed fires.

Unusual Fire and Explosion Hazard:

Dried solids can burn, giving of carbon dioxide, carbon monoxide, aluminum oxide, nitrogen oxide, ammonia and phosphorous oxide. Aluminum flake can react with some acid and caustic solutions to form gas and heat.

REACTIVITY DATA

This product is stable under normal (ambient) conditions and hazardous polymerization will not occur. **Hazardous Decomposition Products:** Combustion of dried film may produce carbon dioxide and carbon monoxide. **Conditions or Materials to Avoid:** None.

SPILL OR LEAK PROCEDURES

Spill: Major spills should be collected for disposal. Minor spills may be flushed to sewer if permitted by local, state, and federal regulations. **Waste Disposal:** Incinerate or bury in suitable landfills where permitted by appropriate government regulations.

SPECIAL PROTECTION INFORMATION

Respiratory Protection: Use appropriate MAHA/NIOSH approved respirator in areas with poor ventilation and when exposed to spray mists or sanding dusts. **Ventilation:** General room ventilation is expected to be satisfactory. Use local exhaust if needed for mist or vapor. **Protective Gloves:** Wear gloves impervious to water and soap. **Eye Protection:** Wear goggles if spraying and available eye bath.

Disclaimer: The information in this MSDS was obtained from sources we believe are reliable. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness. **The conditions or handling, storage, use and disposal of the product** are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product. **Disposal of containers** should be in accordance with applicable federal, state and local laws and regulations.

Thank you for selection Scuffmaster.

technical support: 1.800.898.0219

documents: www.scuffmaster.com



ULTRA CLEAR / CLEAR COAT

MATERIAL SAFETY DATA SHEET



Pretty. Tough. Paint.

PRODUCT IDENTIFICATION

Master Coating Technologies

2740 31st Avenue South

Minneapolis, MN 55406

612.722.8808

Trade Name: **Ultra-Clear Clear Coat**

Chemical Family: Waterbase Acrylic/Urethane Dispersion

Medical & Transport Emergency Contact:

INFOTRAC: 1.800.535.5053

MSDS Date: 07.02.2004

DOT Classification: Not Regulated

Supersedes: All Previous CAS Number: Mixture

Synonyms: UC Satin, UC Gloss

PHYSICAL DATA

Boiling Range (F): 340 (water)

Freezing Point (F): 32 (water)

Vapor Density: N/A

Vapor Pressure: Slower than Ether

Weight / Gallon: 8.65 Pounds

% Volatile by Weight: 67.67

Appearance & Odor: Liquid, latex odor

VOC: 112 g/L

HAZARDOUS INGREDIENTS

Ingredient	Percent	PPM	MG/M3	CAS Number
Butoxy Ethanol	5 - 10	25	.6	00111-76-2

Butoxy ethanol is readily absorbed through skin. Ingestion or absorption may cause red blood cell, liver, and/or kidney damage. This paint mixture often has a polyfunctional aziridine crosslinker added immediately prior to application. This crosslinking agent is an eye and lung irritant. Wear a high-efficiency respirator and goggles when adding crosslinker and when applying product. "Caution-off" the application area to prevent others not wearing protective equipment from exposure to any mist. **See Masterlink MSDS for more details.**

HMIS Rating: Health = 1 Flammability = 0 Reactivity = 0 Personal Protection = B

HEALTH HAZARD DATA

Entry Routes: Inhalation, Ingestion, Skin Contact, Eye Contact **Effects of Overexposure:** N/A **Effects of Inhalation:** Trace component, residual monomer, and other organics may be irritating to the eyes, skin, mucous membranes, respiratory tract and may produce symptoms of headache and nausea in poorly ventilated areas. **Effects of Ingestion:** Irritating to gastrointestinal tract, abdominal pain, and diarrhea. **Effects of Skin Contact:** Prolonged contact can cause transient reddening of the skin. **Effect of Eye Contact:** Direct contact may be irritating to eyes. **Effects of Repeated Overexposure:** This paint mixture as provided shows no evidence of chronic effects from available information.

UC – MATERIAL SAFETY DATA SHEET (continued)

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Immediately flush eyes for 15 minutes occasionally lifting eyelids. If victim wears contact lenses, remove lenses and continue rinsing. Clean lenses before reusing. If irritation continued, consult a physician. **Skin Contact:** Wash effected area thoroughly with mild soap and water. If irritation develops and persists, consult a physician. **Inhalation:** Move to fresh air if necessary. If irritation persists, consult a physician. If victim is not breathing, artificial respiration should be administered by qualified personnel. Seek immediate medical attention. **Ingestion:** If swallowed, give lots of water, and induce vomiting. If necessary consult a physician.

FIRE & EXPLOSION HAZARD DATA

Flash Point: N/A (aqueous system)
LEL: N/A (aqueous system)
OSHA: Non-Flammable
DOT: Non-Combustible

Fire Extinguishing Media:
Use all-purpose foam for large fires, and CO₂ or dry chemical media for small fires.
Special Fire Fighting Procedures: Use breathing apparatus when fighting enclosed fires.

REACTIVITY DATA

Stability: Stable. **Hazardous Polymerization:** Will Not Occur. **Hazardous Decomposition Products:** May produce fumes when heated to decomposition, as in welding or fire. Fumes may contain: carbon monoxide, carbon dioxide, oxides of nitrogen and other products of combustion.

SPILL OR LEAK PROCEDURES

Spill: Major spills should be collected for disposal. Minor spills may be flushed to sewer if permitted by local, state, and federal regulations.
Waste Disposal: Incinerate or bury in suitable landfills where permitted by appropriate government regulations.

SPECIAL PROTECTION INFORMATION

Respiratory Protection: Use appropriate MAHA/NIOSH approved respirator in areas with poor ventilation and when exposed to spray mists or sanding dusts. **Ventilation:** General room ventilation is expected to be satisfactory. Use local exhaust if needed for mist or vapor. **Protective Gloves:** Wear gloves impervious to water and soap. **Eye Protection:** Wear goggles if spraying and available eye bath.

Disclaimer: The information in this MSDS was obtained from sources we believe are reliable. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness. **The conditions or handling, storage, use and disposal of the product** are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product. **Disposal of containers** should be in accordance with applicable federal, state and local laws and regulations.

Thank you for selection Scuffmaster.

technical support: 1.800.898.0219

documents: www.scuffmaster.com

