

Quick Tips.

SCRUBTOUGH APPLICATION GUIDE

Scuffmaster

PRETTY. TOUGH. PAINT.

Application Guide

1.800.898.0219 | On Call Support

Finish Overview

ScrubTough is a waterbased polyurethane-fortified eggshell coating. It is a two component system that must be crosslinked with Masterlink™ crosslinker immediately prior to application. ScrubTough can be brushed, rolled or sprayed.

- **BRUSH:** For brushed applications use quality synthetic fiber brushes.
- ROLL:** For rolled applications, please use quality synthetic fiber roller covers with a 3/8–1/2 inch nap.
- SPRAY:** We recommend using Airless equipment for all sprayed applications with pressure at 2000psi. and a .015”-.021” tip.

Masterlink Additive

Masterlink™ is a performance additive that is added to ScrubTough. Masterlink increases the stain resistance and durability of the finish. Failure to add 2 ounces of Masterlink per gallon will result in a finish that is not as durable as published and will void the warranty.



PRODUCT LIFE ONCE MASTERLINK HAS BEEN ADDED: 36 HOURS - 8 HOURS UNDER PRESSURE

Thinning/Boxing

If needed, thin with water in 2oz increments, max amount 4oz per gallon. Prior to application, box all cans/pails of the same color together.