

FINISH DESCRIPTION

Scuffmaster EnviroMetal Paint is a low odor, low VOC, LEED Compliant metallic paint that is ideal for any interior environment. This innovative hand applied metallic paint is available in two finishes – brushed or rolled – each offering a distinctive, yet elegant look. EnviroMetal Paint is available in thousands of colors, including most of your favorite colors from the Scuffmaster Solid Metal collection.

FEATURES

BENEFITS

Metallic Finish

Effect Elegant and sophisticated and flexible design

Environmentally Responsible

LEED compliant, low-odor application and low-VOC content make Scuffmaster water-base paints compliant with national and international Environmental standards – including the US Green Building Council, Green Seal, California South Coast Air Quality Management District and the European Union

Easy Application

Extremely versatile – applied by hand, either brushed or rolled. NOT TO BE SPRAYED. For sprayed metallic paint, see Scuffmaster’s Solid Metal Finish.

Exceptionally Durable

Cleanable, scrub-able and easy to maintain.

Contractor Friendly

No heavy equipment is required (hand applied)

Textured Finish

Easy repairs

Quick Order Shipment

Most orders (even customs) ship within 24 hours

Warranty

5 – Year manufacturer’s warranty against adhesion failure if product is correctly applied

Class A fire rated

Like all Scuffmaster paints, EnviroMetal is Class A fire rated.

WHERE TO SPECIFY ENVIROMETAL

Corporate Spaces

Corridors
Lobby areas
Offices
Columns
Rooms

Retail Spaces

Interior Walls
Columns
Facades

Entertainment Facilities

Interior Walls
Accent Areas
Feature Walls

Health Facilities

Interior Spaces
Offices
Columns
Rooms

Remember that Scuffmaster Paints are designed for wall surfaces yet can be applied to display fixtures, elevator doors, stairway frames, columns and other architectural elements besides conventional walls.

Suitable Substrates:	Very smooth surfaces for best results. MCT suggests that new sheetrock be prepared to a Level 5 smoothness in accordance with the Gypsum Association's GA214 standard.
Application:	Commercial painting contractors. Must be brushed or rolled, depending upon specified finish. Call your Scuffmaster distributor or MCT for details (800) 898-0219. Natural variation (lighter or darker areas) in installed finish is a characteristic of the product.
Custom Colors:	Yes. No upcharge. Contact your Scuffmaster distributor.

TECHNICAL INFORMATION

System Components	Tinted undercoat (primer/sealer or bonding), base coat (brushed or rolled)
Finish Appearance	Textured finish. Colors may exhibit natural darker/lighter color shades across wall surface.
Colors Available	Thousands of colors. Ability to customize
Application	Commercial painting contractors. Must be brushed or rolled, depending upon specified finish. Call your Scuffmaster distributor or MCT for details (800) 898-0219.
Coverage Rates	Tinted Undercoat - approximately 450 sq. ft. per gallon Base Coat - approximately 250 sq. ft. per gallon depending on app technique
Maximum VOC	<150 g/L
Fire Rating	Under Coat - Class A or 1 (ASTM E-84-91a) Base Coat - Class A or 1 (ASTM E-84-91a)

FIVE YEAR LIMITED WARRANTY

Master Coating Technologies warrants the Scuffmaster components of this finish system against manufacturing defect for a period of five years from the date of application when applied to a wall surface according to manufacturer's printed instructions. Manufacturing defect is defined to be a failure of the coating system to adhere to a wall surface when applied according to manufacturer's printed instructions, and does not include subsequent failure or damage caused by exogenous factors such as substrate failure or defect, sharp objects, persons, or acts of God. In the event of a failure resulting from manufacturing defect, the product will be replaced. Master Coating Technologies shall have no obligation to or otherwise participate in labor or other costs associated with replacing the product. This warranty supersedes all previous warranties.

SAFETY INFORMATION

First Aid: Ingestion – induce vomiting, consult a physician. Skin contact – wash with soap and water. Eye contact – immediately flush eyes for 15 minutes occasionally lifting eyelids. If contact lenses are worn, remove lenses and continue rinsing. Clean lenses before reusing - may not be possible to reuse. Obtain medical attention. Refer to product MSDS and crosslinker MSDS. In case of emergency, call 800-535-5053.

SAFETY INFORMATION

Specifying a Scuffmaster EnviroMetal finish is easy.

1. Call out the Scuffmaster finish color number in your finish schedule or on drawings. Scuffmaster color numbers are printed below each color chip in standard sample cards and on the reverse of every custom sample.
2. Call out the Scuffmaster system components required for the substrate being painted in the "products" section of your specification. The EnviroMetal finish systems for common substrates are listed below.

IMPORTANT: EnviroMetal is a highly reflective finish that, upon application, may exhibit normal color variation that is beyond the control of MCT. Specifically, colors may exhibit slight variation in darkness/lightness upon installation. The degree of surface smoothness prior to product application, applicator technique, and the effects of artificial and natural light sources will also impact the uniformity of finish appearance. New gypsum wallboard may be prepared to a Level 5 finish in accordance with the Gypsum Association's GA214 standard. MCT strongly recommends that specifiers require applicators to prepare a benchmark sample in accordance with PDCA P5-94 "Benchmark Sample Procedure for Paint and Other Decorative Coating Systems." Please refer to the guide specifications for this language.

ENVIROMETAL PAINT SYSTEMS FOR PROPERLY PREPARED SURFACES

1. New Sheetrock:

Prepare to Level 5 finish for best results

Primer - 1 coat Scuffmaster Tinted Undercoat [Primer/Sealer]. Ensure very uniform color across surface.

Base Coat - Scuffmaster EnviroMetal [brushed] [rolled] (applied in two coats)

2. Previously-Painted Surfaces:

Primer – 1 coat of Scuffmaster Tinted Undercoat [Bonding Primer; Primer/Sealer] Call MCT at 800.898.0219.

Base Coat - Scuffmaster EnviroMetal [brushed] [rolled] (applied in two coats)

3. Ceramic Tile:

Primer - 1 coat of Scuffmaster Tinted Undercoat [Bonding Primer]

Base Coat - Scuffmaster EnviroMetal [brushed] [rolled] (applied in two coats)

4. Primed Metal:

Primer – 1 coat of Scuffmaster Tinted Undercoat [Bonding Primer]

Base Coat - Scuffmaster EnviroMetal [brushed] [rolled] (applied in two coats)

5. Un-Primed Metal:

Primer - Call MCT at (800) 898-0219

Base Coat - Scuffmaster EnviroMetal [brushed] [rolled] (applied in two coats)

