

FINISH DESCRIPTION

Durable Eggshell Finish

A premium eggshell finish that attracts attention but repels scuffs and stains. ScrubTough's durable polyurethane formula withstands regular cleaning and keeps walls looking their best.

MICROBAN PROTECTION

ScrubTough contains Microban antimicrobial product protection. This unique additive will inhibit the growth of stain and odor causing bacteria, mold, mildew, and other fungal growth on the dried paint film. Microban protection provides an added level of protection between cleanings, but does not take the place of normal cleaning and disinfecting procedures and will not protect users or others against food-borne illness. Microban additives are E.P.A. registered for use in paint. For more information on Microban, please visit www.microban.com.

FEATURES

BENEFITS

Finish Effect	Rich, durable eggshell
Polyurethane Formulation	Exceptional durability and cleanability
Unlimited Colors	Choose any color from any fandeck
Easy Application	Any quality painting contractor can apply - Brush, roll or spray
Quick Order Shipment	Most orders (even customs) ship within 3 days
Waterbased / Low VOC	Low odor spray application meets all environmental requirements
Warranty	5 – Year manufacturer's warranty against adhesion failure if product is correctly applied
Class A fire rated	Like all Scuffmaster paints, ScrubTough is Class A fire rated.

WHERE TO SPECIFY SCRUBTOUGH

Remember that Scuffmaster Paints are designed for wall surfaces yet can be applied to display fixtures, elevator doors, stairway frames, columns and other architectural elements besides conventional walls.

Corporate Spaces

Corridors
 Offices
 Lobby areas
 Conference rooms
 Cafeterias
 Lunch rooms
 Bathrooms
 Stairwells

Educational Facilities

Corridors
 Offices
 Lecture halls
 Auditoriums
 Gymnasiums
 Locker rooms
 Bathrooms
 Dormitories

Healthcare Facilities

Corridors
 Offices
 Waiting areas
 Examination rooms
 Meeting rooms
 Cafeterias
 Bathrooms
 Stairwells

Other Applications

Theaters
 Exercise rooms
 Pool areas
 Escalator areas
 Elevator areas
 Passenger terminals
 Baggage claim areas
 Parking areas

Suitable Substrates:

Primed sheetrock, previously painted surfaces, concrete block, metal, ceramic tile, glazed block and others.

Application:

Finish can be brushed, rolled or sprayed. Call your Scuffmaster distributor or MCT for details and applicators in your area (800) 898-0219.

Custom Colors:

Yes. No up-charge. Contact your Scuffmaster distributor.

TECHNICAL INFORMATION**System Components**

Finish Coat

Finish Appearance

Rich eggshell

Colors Available

Can match any color from any fan deck

Application

Finish can be brushed, rolled or sprayed. Call your Scuffmaster distributor or MCT for details and applicators in your area (800) 898-0219.

Coverage Rates

Approximately 350 ft²/gal. (deep/bright colors require additional coats)

Maximum VOC

< 49 g/L

Fire Rating

Class A or I

ASTM E-84-91a

Scrub Resistance:

8,000 Scrub Cycles

ASTM D 2486

Stain Removal:

Excellent Rating for most stains

4-Hour Open Spot Test

FIVE YEAR LIMITED WARRANTY

Master Coating Technologies warrants the Scuffmaster components of this finish system against manufacturing defect for a period of five years from the date of application when applied to a wall surface according to manufacturer's printed instructions. Manufacturing defect is defined to be a failure of the coating system to adhere to a wall surface when applied according to manufacturer's printed instructions, and does not include subsequent failure or damage caused by exogenous factors such as substrate failure or defect, sharp objects, persons, or acts of God. In the event of a failure resulting from manufacturing defect, the product will be replaced. Master Coating Technologies shall have no obligation to or otherwise participate in labor or other costs associated with replacing the product. This warranty supersedes all previous warranties.

SAFETY INFORMATION

Some persons may experience an allergic reaction to paint products if exposed to spray mist. Because spray application of this Scuffmaster finish may create a fine mist of product and product catalyst in the immediate application area, a high-efficiency particulate respirator and protective glasses or goggles should be worn by the applicator. The immediate application area should be "cautioned-off" to prevent persons without safety equipment from coming into contact with mist. Ensure good ventilation. Product MSDS sheets are available from MCT by calling (800) 898-0219.

First Aid: Ingestion – induce vomiting, consult a physician. Skin contact – wash with soap and water. Eye contact – immediately flush with clean water for 15 minutes occasionally lifting eyelids. If contact lenses are worn, remove lenses and continue rinsing. Clean lenses before reusing - may not be possible to reuse. Obtain medical attention. Refer to product MSDS and crosslinker MSDS. In case of emergency, call 800-535-5053.

HOW TO SPECIFY SCRUBTOUGH

Specifying a Scuffmaster ScrubTough finish is easy.

1. Call out the Scuffmaster finish color number in your finish schedule or on drawings. Scuffmaster color numbers are printed below each color chip in standard sample cards and on the reverse of every custom sample.
2. Call out the Scuffmaster system components required for the substrate being painted in the "products" section of your specification. The Scuffmaster ScrubTough finish system for common substrates are listed below.

IMPORTANT: Make it very clear in your specification that only manufacturer-approved applicators can apply Scuffmaster ScrubTough finishes. Non-approved applicators should be referred to the local Scuffmaster distributor or to MCT at (800) 898-0219 before submitting a bid on a product with which they are not familiar. MCT strongly recommends including proper applicator qualification submittal procedures, finish submittal procedures and surface preparation steps in your specification. Please refer to the guide specifications for this language.

SCRUBTOUGH FINISHES FOR PROPERLY PREPARED SURFACES

1. New Sheetrock:

Primer - 1 coat Scuffmaster Primemaster Primer/Sealer

1-2 coats of Scuffmaster ScrubTough Performance Paint with Microban (at least 2 coats if bright, deep or dark color)

2. Cured Concrete/Masonry:

Primer - 1 coat of 100% latex acrylic block filler (if required to seal surface for better coverage)

1-2 coats of ScrubTough Performance Paint with Microban (at least 2 coats if bright, deep or dark color)

3. Wood

Primer – Spot-prime knots and prime with 1 coat of a suitable stain-blocking primer

1-2 coats of ScrubTough Performance Paint with Microban (at least 2 coats if bright, deep or dark color)

4. Hard Shiny Surfaces:

Primer - 1 coat of Scuffmaster Primemaster Bonding Primer 1-2 coats of ScrubTough Performance Paint with Microban (at least 2 coats if bright, deep or dark color)

5. Previously Painted Surfaces:

Primer - 1 coat Scuffmaster Primemaster Primer/Sealer may be desirable to extend coverage and/or provide a uniform sealed surface 1-2 coats coat of ScrubTough Performance Paint with Microban (at least 2 coats if bright, deep or dark color)

CLEANING INSTRUCTIONS

Allow product to cure for at least seven days following application (allow 28 days on hard, non-absorbent substrates) before applying cleaning chemicals. Most common stains can be removed using warm water and detergent. More difficult stains may require stronger cleaners and a light abrasive pad. Before using a new cleaner for the first time, test its effect on the finish by applying in an inconspicuous area as a small amount of paint may also be removed during the cleaning process.

